

School Toilets

Kestrel Court Harbour Road Portishead Bristol BS20 7AN

Phone: 01275 400456

Web: https://www.school-toilets.co.uk Email: sales@school-toilets.co.uk

RWF3000 Replacement Water Filter



Product Code: RWF3000

RWF3000 High-Capacity PFAS & Contaminant Water Filter

Product Code: RWF3000

 $Compatible \ with \ Washware \ Essentials \ Models: \ \underline{WCWM \ water \ cooler} \ and \ \underline{WCBF \ bottle \ filler \ cooler}.$

Why Choose the RWF3000?

The RWF3000 is a premium-grade replacement water filter cartridge, built on the proven filtration technology of Murdock's 3,000-gallon PFAS filter. Designed for demanding environments, it delivers superior water quality and peace of mind for your WCWM and WCBF systems.

Key Features & Benefits

Two-Stage Filtration - The RWF3000 uses a dual-stage design combining hollow core fiber and a carbon block to deliver robust performance.

Broad Contaminant Reduction - PFAS: Reduces total PFAS, including PFOA, PFOS, PFHpA, PFHxS, and PFNA.

Lead: Greater than 99.7% reduction at rated test conditions.

Chlorine & Taste/Odour: Meets NSF/ANSI 42 standard for taste, smell, and particulates.

Cysts / Bacteria: Certified to remove microorganisms to 0.1 micron (99.9% bacteria removal) via ASTM F838-20.

Microplastics: Certified reduction under NSF/ANSI 401.

Long Service Life: Rated for up to 3,000 gallons (approx. 11,356 litres), or one year, whichever comes first.

Solid Flow Rate: Maximum permitted flow rate of 1.25 GPM (~1.9 L/min), ensuring good water delivery during peak use.

Temperature & Pressure

- Tested for use in the range of 2 °C to 38 °C.
- Maximum operating pressure: 105 PSIG (724 kPa).

Easy Replacement

• Twist-in cartridge design with a hygienic cap for safe handling.

Certifications

• Complies with NSF/ANSI standards: 42, 53, 401, and also meets ASTM F838-20 for bacterial reduction.

Installation & Maintenance

Installation:

- Ensure the filter is used for cold water only (maximum 38 °C) to protect integrity.
- Insert the cartridge into the filter head and twist clockwise until it locks into place.
- After fitting, flush approximately 23 litres (6 US gallons) before use: per Murdock instructions, either 12 minutes via bubbler or 6 minutes via bottle filler.

Replacement

- Replace the RWF3000 every 12 months or when the 3,000-gallon capacity is reached, or sooner if flow noticeably drops.
- Do not use with water of unknown microbial quality without disinfection before or after filtration.

Compatibility with Washware Essentials

- WCWM (Washware Water Cooler Model) and WCBF (Washware Bottle Filler).
- The RWF3000 integrates seamlessly into these systems, providing your users with high-quality filtered water while leveraging Murdock's proven filter design.
- Filter Housing: Your system must support a filter head compatible with Murdock-style cartridges (or the appropriate adapter) to properly mount the RWF3000.

Safety & Regulatory Notes

- Ensure installations comply with local plumbing regulations.
- · Use only with cold water supply.
- Protect the filter from freezing.
- Follow wash and flush procedure after installation to avoid any initial fine carbon dust.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.

All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**