School Toilets
5 Brearley Court, Baird Road Waterwells Business Park Gloucester GL2 2AF
Phone: 01275 400456
Web: https://www.school-toilets.co.uk
Email: sales@school-toilets.co.uk

Fibreglass Drinking Fountain - White (Non-Chilled)





Product Code: GRP-DF

White GRP Wall Mounted Drinking Fountain with WRAS Approved Tap

This white GRP wall mounted drinking fountain is a reliable choice for school washrooms, sports facilities and other shared environments where strength, hygiene and ease of maintenance are important. Made from robust fibreglass, it offers a lightweight but hard-wearing alternative to metal units and is designed to stand up to regular use in busy locations.

Complete with a WRAS approved push-button tap, the fountain supports safe drinking water provision and helps meet UK water standards. Its neat wall mounted design saves floor space, while the integrated splashback and smooth surfaces make cleaning quick and straightforward.

Delivery

Fast mainland UK delivery, typically within 1 - 2 working days

Tech Specs

Durable GRP/fibreglass body designed for long service life
Wall mounted format keeps the floor area clear and easy to clean
WRAS approved bubbler tap for reassurance on water regulation compliance
Smooth white finish gives a clean, bright appearance
Rounded front edge helps improve safety in pupil and public areas
Built-in rear upstand helps reduce splashing onto surrounding walls
Resistant to corrosion and suitable for demanding washroom environments
Lightweight design makes handling and installation easier than many metal alternatives
Ideal for schools, colleges, leisure centres, swimming pools workplaces and public buildings

What's Included

White fibreglass drinking fountain body
WRAS approved push-button drinking tap
Concealed wall fixing bracket
32mm waste outlet

Extras

32mm plastic bottle trap
32mm chrome plated brass bottle trap with chrome brass pipe and wall flange
Y strainer

Inline water filter

Installation Note:

For best performance, we recommend fitting a Y strainer or inline filter to help protect the valve and maintain the correct flow rate. In cold conditions, the unit should be isolated and drained to avoid frost damage. Failure to fit suitable filtration may affect the product warranty.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**